



# 17.609 G

## OEM Pressure Transmitter

### Application:

- ▶ refrigeration

### Characteristics:

- ▶ stainless steel sensor, welded
- ▶ accuracy 0.5 % FSO according to IEC 60770
- ▶ nominal pressure ranges from  
 0 ... 6 bar up to 0 ... 60 bar  
 -1 ... 6 bar up to -1 ... 60 bar

### Technical Data



Pressure ranges							
Nominal pressure gauge	[bar]	6	10	16	25	40	60
Overpressure	[bar]	14	35	35	70	140	140
Burst pressure ≥	[bar]	28	70	70	140	280	280
Vacuum resistance		unlimited					
Vacuum ranges							
Nominal pressure gauge	[bar]	-1 ... 6	-1 ... 10	-1 ... 16	-1 ... 25	-1 ... 40	-1 ... 60
Overpressure	[bar]	14	35	35	70	140	140
Burst pressure	[bar]	28	70	70	140	280	280
Output signal / Supply							
Standard		2-wire: 4 ... 20 mA		/ V <sub>S</sub> = 8 ... 32 V <sub>DC</sub>			
Options 3-wire		3-wire: 0 ... 10 V		/ V <sub>S</sub> = 14 ... 30 V <sub>DC</sub>			
		3-wire ratiometric: V <sub>Sig</sub> = 0.5 ... 4.5 V		/ V <sub>S</sub> = 5 ± 0.5 V <sub>DC</sub>			
Performance							
Accuracy <sup>1</sup>		≤ ± 0.5 % FSO					
Permissible load		2-wire: R <sub>max</sub> = [(V <sub>S</sub> - V <sub>S min</sub> ) / 0.02] Ω			3-wire: R <sub>min</sub> = 10 kΩ		
Influence effects		supply: 0.05 % FSO / 10 V			load: 0.05 % FSO / kΩ		
Response time		2-wire: ≤ 10 msec			3-wire: ≤ 3 msec		
Measuring rate		1 kHz					
<sup>1</sup> accuracy according to IEC 60770 – limit point adjustment (non-linearity, hysteresis, repeatability)							
Thermal effects (Offset and Span) / Permissible temperatures							
Thermal error		≤ ± 0.3 % FSO / 10 K		in compensated range		0 ... 70 °C	
Permissible temperatures		medium: -40 ... 125 °C		electronics / environment: -40 ... 85 °C		storage: -40 ... 85 °C	
Electrical protection							
Short-circuit protection		permanent		3-wire ratiometric: none			
Reverse polarity protection		no damage, but also no function					
Electromagnetic protection		emission and immunity according to EN 61326					
Mechanical stability							
Vibration		20 g, 25 Hz ... 2 kHz		according to DIN EN 60068-2-6			
Shock		500 g / 1 msec		according to DIN EN 60068-2-27			

# 17.609 G

OEM Pressure Transmitter

Technical Data

Materials				
Pressure port	stainless steel 1.4571			
Housing	stainless steel 1.4301			
Seal of sensor	none (welded)			
Diaphragm	stainless steel 1.4542			
Media wetted parts	pressure port, diaphragm			
Miscellaneous				
Mechanical connection	7/16"-20 UNF			
Weight	approx. 120 g			
Current consumption	2-wire: max. 25 mA		3-wire ratiometric: typ. 3 mA	
	3-wire voltage: typ. 5 mA (short circuit current: max. 20 mA)			
Long term stability	$\pm 0.3\%$ FSO / year at reference conditions			
Operational life	$> 100 \times 10^6$ pressure cycles			
CE-conformity	EMC Directive: 2004/108/EC			
Wiring diagrams				
<p>2-wire-system (current)</p>		<p>3-wire-system (voltage)</p>		
Pin configuration				
Electrical connection	ISO 4400	Micro (contact distance 9.4 mm)	M12x1 (4-pin), plastic	cable colours (DIN 47100)
Supply +	1	1	1	wh (white)
Supply -	2	2	2	bn (brown)
Signal + (for 3-wire)	3	3	3	gn (green)
Shield	ground pin	ground pin	4	gn/ye (green / yellow)
Dimensions (in mm)				
<p>ISO 4400 (IP 65)</p>		<p>Micro, contact distance 9.4 mm (IP 65)</p>		<p>M12x1, 4-pin (IP 67)</p>
				<p>cable outlet with PVC-cable (IP 67)<sup>2,3</sup></p>
<p><sup>2</sup> standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70 °C)</p> <p><sup>3</sup> different cable types and lengths available, permissible temperature depends on kind of cable</p>				

This data sheet contains product specification, properties are not guaranteed. Subject to change without notice.



**17.609 G**

**17.609 G** - ---------

<b>Eingang</b>													<b>[bar]</b>								
	6	6	0	0	1																
	10	1	0	0	2																
	16	1	6	0	2																
	25	2	5	0	2																
	40	4	0	0	2																
	60	6	0	0	2																
	-1 ... 6	V	6	0	2																
	-1 ... 10	V	1	0	3																
	-1 ... 16	V	1	6	3																
	-1 ... 25	V	2	5	3																
	-1 ... 40	V	4	0	3																
	-1 ... 60	V	6	0	3																
	Sondermessbereiche	9	9	9	9												auf Anfrage				
<b>Messgröße</b>													relativ			R					
<b>Ausgang</b>													4 ... 20 mA / 2-Leiter			1					
													0 ... 10 V / 3-Leiter			3					
													0,5 ... 4,5 V / 3-Leiter ratiometrisch			R					
<b>Genauigkeit</b>													0,5 % FSO			5					
													andere			9			auf Anfrage		
<b>Elektrischer Anschluss</b>													Stecker und Kabeldose ISO 4400			1 0 0					
													Stecker und Kabeldose Micro			C 1 0					
													Stecker M12x1 (4-polig), Kunststoff			M 0 0					
													Kabelausgang mit PVC-Kabel			T A 0					
													andere			9 9 9			auf Anfrage		
<b>Mech. Anschluss / Dichtung</b>													7/16"-20 UNF			U 0 0 2					
													andere			9 9 9 9			auf Anfrage		
<b>Sonderausführungen</b>													Standard			0 0 0					
													andere			9 9 9			auf Anfrage		

<sup>1</sup> Standard: 2 m PVC-Kabel ohne Belüftungsschlauch (Temperaturreinsatzbereich: -5 ... 70 °C)

Die Angaben dieser Preisliste enthalten die Spezifikation der Produkte, nicht die Zusicherung von Eigenschaften. Ausführliche Informationen zu den Bestelloptionen können dem Datenblatt entnommen werden. Technische Änderungen vorbehalten.