LR SMART TECH Hydraulic Diagnostic Device Pressure - Flow Rate - Temperature

HD 01

Rel. 20240724

Hydraulic Diagnostic Device HD 01

for testing and diagnostic works in hydraulic systems

- 2 measuring channels
- Per measuring channel display of 3 physical quantities:
 Pressure (P) + Flow rate (Q) + Temperature (T)
 Accuracy of pressure measurement: ±0.5% FS
 Accuracy of flow rate and temperature measurement: ±2% FS
- Logging and storage of measured data via USB interface on USB stick
- The integrated chargeable Li-Ion battery guarantees long time autonomeous operation
- Clear, easy reading LC display, with backlight option
- Operation via easy manageable keypad
- Measuring rate: 1 ms (1 measurement every 0.001 s)
- Data storage rate: 100 ms
- Sensors supplied with factory certificate of calibration





HD-01-SET-01

- Handheld device HD 01
- Sensor package
 Pressure: 0...250 bar (±0.5% FS)
 Flow rate: 7,5...75 l/min (±2% FS)
 Temperature: 0...125°C (±2% FS)
- Battery charger
- USB stick
- Factory certificate of calibration
- Carrying case with foam inserts

HD-01-SET-02

- Handheld device HD 01
- Sensor package
 Pressure: 0...400 bar (±0.5% FS)
 Flow rate: 15...300 l/min (±2% FS)
 Temperature: 0...125°C (±2% FS)
- Battery charger
- USB stick
- Factory certificate of calibration
- Carrying case with foam inserts

HD-01-SET-04

- Handheld device HD 01
- Sensor package
 Pressure: 0...400 bar (±0.5% FS)
 Flow rate: 7,5...75 l/min (±2% FS)
 Temperature: 0...125°C (±2% FS)
- · Battery charger
- USB stick
- Factory certificate of calibration
- Carrying case with foam inserts

HD-01-SET-03

- Handheld device HD 01
- Sensor package
 Pressure: 0...400 bar (±0.5% FS)
 Flow rate: 40...600 l/min (±2% FS)
 Temperature: 0...125°C (±2% FS)
- Battery charger
- USB stick
- Factory certificate of calibration
- Carrying case with foam inserts

HD 01

LR-SMART TECH Hydraulic Diagnostic Device Pressure - Flow Rate - Temperature







Hydraulic Diagnostic Device HD 01 Sets / Spare parts / Accessories

my and a modern Detroit in Detroit y open to part of the	
Content - Hydraulic Diagnostic Device HD 01 Sets	Order-Code:
 Set 1: • HD 01 Hydraulic Diagnostic basic Device • Sensor package 7,575 l/min + 0250 bar + 0125°C • Charger • USB stick • Transport case with foam insert 	HD-01-SET-01
 Set 2: • HD 01 Hydraulic Diagnostic basic Device • Sensor package 15300 l/min + 0400 bar + 0125°C • Charger • USB stick • Transport case with foam insert 	HD-01-SET-02
 Set 3: • HD 01 Hydraulic Diagnostic basic Device • Sensor package 40600 I/min + 0400 bar + 0125°C • Charger • USB stick • Transport case with foam insert 	HD-01-SET-03
 Set 4:	HD-01-SET-04
Components and Spare Parts for HD 01:	Order-Code:
HD 01 Hydraulic Diagnostic basic Device (without sensors etc.)	HD-01
Sensor package 7,575 l/min + 0250 bar + 0125°C	HD-01-SP-075
Sensor package 15300 l/min + 0400 bar + 0125°C	HD-01-SP-300
Sensor package 40600 l/min + 0400 bar + 0125°C	HD-01-SP-600
Pressure sensor (single) for HD 01: Range 0250 bar	HD-01-DS-0250
Pressure sensor (single) for HD 01: Range 0400 bar	HD-01-DS-0400
Pressure sensor (single) for HD 01: Range 0600 bar	HD-01-DS-0600

DRUCK & TEMPERATUR Leitenberger GmbH • Bahnhofstr. 33 • D-72138 Kirchentellinsfurt • GERMANY Tel. +49 (0) 7121-90920-0 • Fax +49 (0) 7121-90920-99 • DT-Export@Leitenberger.de • **www.druck-temperatur.de**