

Pressure Comparison Pump LPP 60-T Generating pressure -0,95...+60 bar (870 psi)

LPP 60-T

Rel. 20241129

Pressure Comparison Test Pump LR-Cal LPP 60-T, pneumatic Generation of test pressure up to +60 bar (870 psi), switchable to Generation of vacuum to -0.95 bar (-28 inHg)

The Calibration Test Pump LR-Cal LPP 60-T is used to generate pressures and vacuum for checking, adjusting and calibrating mechanical and electronic pressure measuring instruments by comparative measurements. These pressure tests may be carried out in laboratories, workshop or on site at the measuring point. If the instrument under test and a sufficiently accurate reference measuring instrument is connected to the LR-Cal LPP 60-T, the same pressure/ same pressure / vacuum is applied to the two instruments when the pump is operated.

Despite its compact dimensions, the calibration test pump LR-Cal LPP 60-T is easy to operate and allows for exact generation of the required test pressures. A change-over switch enables the generation of vacuum as well. The LR-Cal LPP 60-T is fitted with a fine adjustment valve for the precise adjustment of pressures. The reference instrument is screwed directly on to the top of the pump and the unit under test is connected by means of a connection tube incorporating an adapter 1/4" BSP rotating female (optional 1/4" NPT female) port.

Specification:

Pressure generation: Vacuum generation: Pressure ports:	 060 bar = 0870 psi (or equivalent), switchable to 0 0,95 bar = 028 inHG (or equivalent) 1/2" BSP female rotating (with seal) for reference instrument on the top of the pump (Type LPP-60-T-N14: 1/4" NPT female, type LPP-60-T-G14: 1/4" BSP female rotating) 1/4" BSP female for unit under test (at connection tube) (Type LPP-60-T-N14: 1/4" NPT female)
Volume per stroke:	appr. 11 cm ³
Materials:	anodized aluminum, brass (chromium plated)
Fine adjustment:	Fine adjustment valve
Dimension:	appr. 150 x 300 x 215 mm
Weight:	appr. 2.55 kg

Included in standard supply:

- Calibration test pump LR-Cal LPP 60-T
- Connection tube with female rotating pressure port
- Operating manual

Optional accessories:

- Set of adapters and seals for unit under test
- Carrying case with custom foams
- · Tool for a simple operation of the adjustment valve (LPP-VOLUMEN-TOOL)

Recommended Reference Instruments:

- Accuracy ±0.05/0.1% F
- Accuracy ±0.050% FS:
- Accuracy ±0.1% FS:
- Accuracy ±0.2% FS:
- Accuracy ±0,125% BFSL
- Accuracy ±0,25% BFSL
- Accuracy ±0.6% FS Accuracy ±1.0% FS:
- Electronic Pressure Calibrator **TLDMM-2.0** Digital Test Pressure Gauge **TLDMM-A01** Digital Test Pressure Gauge **TLDMM-A02** Digital Test Pressure Gauge LDM70-E25 Digital Test Pressure Gauge Analogue Pressure Gauge Analogue Pressure Gauge

Handheld Pressure Calibrator LHM LDM70-K50 LPP-MANO-K06 LPP-MANO

datasheet "LHM" datasheet "TLDMM 2.0" datasheet "LDM 80" datasheet "LDM 80" datasheet "LMD 70" datasheet "LDM 70" see reverse page see reverse page

DRUCK & TEMPERATUR Leitenberger GmbH • Bahnhofstr. 33 • D-72138 Kirchentellinsfurt • GERMANY Tel. +49-7121-90920-0 • Fax +49-7121-90920-99 • DT-Export@Leitenberger.de • www.druck-temperatur.de

LPP 60-T

Pressure Comparison Pump LPP 60-T Generating pressure -0,95...+60 bar (870 psi)



Order-Codes:

Description	Order Code
LR-Cal LPP 60-T Calibration Test Pump -0,95+60 bar (-28 in Hg+870 psi) NOTE: if you dismount the reference connector, you get 3/8" BSP female port	LPP-60-T
ditto, but reference port 1/4" BSP female rotating	LPP-60-T-G14
ditto, but reference port and test port 1/4" NPT female	LPP-60-T-N14
Set of BSP adapters and set of seals 1/8" BSP, 3/8" BSP and 1/2" BSP	LPP-ADAPTER-BSP
Set of metric adapters and set of seals M12x1,5 M20x1,5 and Minimess [®]	LPP-ADAPTER-M
Set of NPT adapters 1/8" NPT, 1/4" NPT, 3/8" NPT, 1/2" NPT	LPP-ADAPTER-NPT
Tool to simplify operation	LPP-VOLUMEN-TOOL

of the fine adjustment valve

Carrying case with foams

-1...0 bar/inHg; -1...+39 bar/PSI

To mount the reference instruments

or LPP-MANO you do not need any adapter if you use the calibration handpump type LR-Cal LPP 60-T, order-code LPP-60-T.

±1% FS, fine graduation dial.

NOTE:

LPP-MANO-K06 analogue reference gauge DS 100

LPP-MANO analogue reference gauges DS 63

0...40 bar/PSI; -1...0 bar/inHg; -1...+39 bar/PSI Spare part: Test tube with 1/4" BSP female port

Spare part: Fine adjustment valve with relief valve

Service Kit for LR-Cal LPP 60-T (O-rings, seals, etc.)

LR-Cal TLDMM 2.0, LR-Cal LDM 80, LR-Cal LDM 70

±0.6% FS, all stainless steel, fine graduation dial. Incl. certificate Available ranges: 0...4 bar/PSI; 0...25 bar/PSI; 0...40 bar/PSI;

Available ranges: 0...2 bar/PSI; 0...11 bar/PSI; 0...25 bar/PSI;





LPP-60-T-KOFFER

LPP-MANO-....-K06



LPP-MANO-....

LPP-SCHLAUCH-S-0050 LPP-VENTIL LPP-WARTUNG





(1) pressure port for mounting reference pressure instrument

- (2) fine volume adjustment, for generating high pressure appr. 40...60 bar and fine pressure adjustment
- (3) pressure relief valve

2

- (4) Switch pressure generation / vacuum generation
- (5) pressure port for test item
- (6) pump to generate pressure up to appr. 40 bar

DRUCK & TEMPERATUR Leitenberger GmbH • Bahnhofstr. 33 • D-72138 Kirchentellinsfurt • GERMANY Tel. +49-7121-90920-0 • Fax +49-7121-90920-99 • DT-Export@Leitenberger.de • www.druck-temperatur.de