


Pressure Gauge Cocks male/female (adjusting nut)


Rel. 20180702

Type	Connection thread	PN	Material	Part no.	Remarks
<p>DIN 16 262-B</p>	G 1/4	6	brass	003.2.000.0000.0	
<p>DIN 16 262-A</p>	G 1/2	25	brass steel stainless steel	003.3.000.0000.0 003.3.010.0000.0 003.3.020.0000.0	
<p>DIN 16 263-A</p>	G 1/2	25	brass steel stainless steel	003.3.310.0000.0 003.3.311.0000.0 003.3.312.0000.0	with test connection M 20 x 1,5 and protecting cap D DIN 16 287
	G 1/2	25	brass steel stainless steel	003.3.360.0000.0 003.3.361.0000.0 003.3.362.0000.0	with test flange 60 x 25 x 10 mm
	G 1/2	25	brass	003.3.800.0000.0	with test flange Ø 40 x 5 mm


The operating positions are engraved on the plug:




vent



operate



purge



test
(only cock with test connection)






- Range of application:

For liquids, gas or steam, from - 10°C up to + 50°C
For pressure gauges with sealing washer according to DIN 16 258


- Plastic handle

- **Please note:** The types made of brass have an adjusting nut and a protecting cap made of phosphatized steel.


Pressure Gauge Cocks male/female

Type	Connection thread	PN	Material	Part no.	Remarks
	G 1/4	6	brass	003.2.700.0000.0	
	G 3/8	16	brass	003.5.900.0000.0	
DIN 16 261-B 	G 1/2	25	brass	003.1.500.0000.0	
	G 1/2	25	stainless steel	003.1.520.0000.0	
	G 1/2	25	brass	003.1.700.0000.0	with test flange 60 x 25 x 10 mm
	G 1/2	25	brass	003.4.700.0000.0	with test flange Ø 40 x 5 mm


The operating positions are engraved on the plug:




vent



operate



purge

test
(only cock with
test connection)

- Range of application:


For liquids, gas or steam, from - 10°C up to + 50°C
For pressure gauges with sealing washer according to DIN 16 258

- Plastic handle


Pressure Gauge Cocks **female/female**

Type	Connection thread	PN	Material	Part no.	Remarks
	G 1/4	6	brass	003.2.400.0000.0	
	G 3/8	16	brass	003.5.800.0000.0	
	G 1/2	25	brass	003.1.300.0000.0	
	G 1/2	25	stainless steel	003.1.320.0000.0	
	G 1/2	25	brass	003.1.600.0000.0	with test flange 60 x 25 x 10 mm
	G 1/2	25	brass	003.0.460.0000.0	with test flange Ø 40 x 5 mm


The operating positions are engraved on the plug:




vent



operate



purge



test
(only cock with
test connection)

- Range of application:


For liquids, gas or steam, from - 10°C up to + 50°C
For pressure gauges with sealing washer according to DIN 16 258

- Plastic handle


Pressure Gauge Cocks male/female (swivel nut)

Type	Connection thread	PN	Material	Part no.	Remarks
	G 1/2	25	brass	003.1.900.0000.0	
	G 1/2	25	brass	003.1.400.0000.0	with test flange 60 x 25 x 10 mm
	G 1/2	25	brass	003.2.200.0000.0	
	G 1/2	25	brass	003.1.800.0000.0	with test flange 60 x 25 x 10 mm


The operating positions are engraved on the plug:




vent



operate



purge



test
(only cock with test connection)

- Range of application:

For liquids, gas or steam, from - 10°C up to + 50°C
For pressure gauges with sealing washer according to DIN 16 258

- Plastic handle